

INTERACTIVE FLOOR MOUNT SERVICE KIOSK

Enjoy seamless **Cloud Network**
for every single device with **FREE**
Content Management Software



Key Features

- **Open Android 11** and above
- **Signage** and **Third Party** Applications
- Content Management System by **LAN**
- Content Management System by **Cloud**
- 58 mm **kiosk printer**
- Built-in **Audio**
- 10 points **Capacitive Touch / IR Touch**
- Horizontal **split screen** available by CMS

Application Area

Healthcare | Educational Institutions
Hotels & Restaurants | Financial Institutions
Entertainment Zone | Corporate Area
Shopping Malls | Reception and Lounge Area



Sizes Available

17.5 | 21.5 | 24

Display Panel Specifications

Features	Model No. CIA-175T-FMSKPM	Model No. CIA-215T-FMSKPM	Model No. CIA-240T-FMSKPM
Panel Size	17.5 inch	21.5 inch	24 inch
Panel Type	TFT LCD	TFT LCD	TFT LCD
Resolution	1080 x 1920	1080 x 1920	1080 x 1920
Contrast Ratio	800 : 1	1000 : 1	1000 : 1
Viewing Angle	178°	178°	178°
Luminance	250 nits	250 nits	300 nits
Aspect Ratio	9 : 16	9 : 16	9 : 16
Display colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors
Display mode	Transmission mode, Normally Black	Transmission mode, Normally Black	Transmission mode, Normally Black
Active area (W x H) (mm)	270.34 x 337.92	268.11 x 476.64	324 x 518.4
Operating Temperature	0 °C - +50 °C	0 °C - +50 °C	0 °C - +50 °C
Storage Temperature	-20 °C - +60 °C	-20 °C - +60 °C	-20 °C - +60 °C
Operating Ambient Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH
Storage Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH

Software specifications

Operating system	Android 10.0 & above
Audio	Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP and other formats
Video	Support AVI, rm, rmvb, MKV, WMV, MOV, MP4, DAT, PMP, MPEG, MPG, FLV, ASF, TS, TP, 3GP, MPG and other formats
Image	Support various image formats such as JPG, BMP, PNG
System comes with application software	APK Installer, Email, Calculator, Browser, Recorder, Calendar, Settings, Clock, Video Player, Search, Contacts, Gallery, Download, Camera, Music, Explorer, etc.
Language	Support multi-language
Input method	Standard Android Keyboard with optional third-party input method
System Management	Original ecological Android system, open root permissions, and can customize product development Real-time remote monitoring, system crash self-recovery, unattended 7 x 24 hours Support OTA remote upgrade; support U disk upgrade Support server / stand-alone mode switching Support WI-Fi hotspot
System watchdog	Support software watchdog

Hardware Specifications

CPU & Chipset	RK 1.8 Ghz & above 64 bit high performance CPU
GPU	Mail-G55/T864/T764 (Optional) high performance GPU
Memory	Default 2 GB 4 GB (Optional)
Built-in storage capacity	Default 32 GB 64 GB (Optional)
Network	Adaptive 10/100 mbps 100/1000 mbps Ethernet
Wifi	Support 2.4G / 5G, Wi-Fi, support Wi-Fi 802.11b/g/n protocols
Image rotation	Support manual rotation of 0 degree, 90 degree, 180 degree, 270 degree
Display	TFT LCD Professional Signage Panel (Industrial Grade) 16.7M colours 8-bit colour depth 178 degree viewing angle 24 x 7 operation support Ultra slim metal body
HDMI	HDMI (Out) / HDMI (In) optional
Audio	10W x 2 speaker
Power amplifier	2 outputs (8 ohms, 10 watts dual audio amplifier output)
Microphone	Differential MIC input
Touch screen (Optional)	Support USB multi-point infrared touch, multi-point capacitive touch, multi-point nano film touch, multi-point acoustic wave touch, multi-point optical touch and more.
RCT	Built-in real-time clock function
USB	2 x USB (USB 3.0)
Infrared	Support infrared remote control function
LED	1* power status LED (green), 1* system LED (green / blue blinking in default)
Bluetooth	Support 4.2 bluetooth
I/O	Support 5 IO input and output control, can be used as key scanning control
Serial port	30 pin FPC interface, Largest support 1300 w Camera
Power Adapter	Input : AC 100-240 V 50-60 HZ, Output : DC 12 V 1.5 A (Requires surge voltage less than 18 V and ripple voltage less than 100 mV)
Optional hardware	Camera, Sensor, QR Scanner, Printer etc.

Electrical & Physical Specifications

Electrical & Physical specification			17.5"	21.5"	24"
Input Power Supply	220 V - 240 V 1 Ph. 50 Hz	Dimensions (W x D x H)	- (mm)	- (mm)	- (mm)
Operating Voltage	12 V DC	Base (W x D x H)	- (mm)	- (mm)	- (mm)
Standby	0.5 W	Gross Weight	-	-	-
		Cabinet Material	MS	MS	MS

INTERACTIVE FLOOR MOUNT SERVICE KIOSK Specification

Product Introduction

FP302 is a kind of 3 inch panel mounted (mounting in front panel of the device) printer, can print 58 mm and 80 mm paper width. This is most used as Kiosk Printer in Queue management system, self-ordering kiosk, visitor attendance terminal, ticket vendor, information kiosk, check-in kiosk, vehicle-mounted ticket vendor and more. This printer has paper jam detection system, support easy paper loading option by a front switch panel with a speed of 250 mm/s. This thermal printer supports all Operating system like Android, Windows, Linux/Ubuntu. The connectivity is as easy like using a 2 pin connector / USB / RS 232 for easy operations.



Features

- Brand name printer mechanism & auto cutter
- Rugged industrial shell
- Ultra fast speed 250 mm/s
- Multi-position location hole mounting
- Patented "anti-block" ticket system
- Suitable for vehicle-mounted environment
- Adjustable bucket for 58/80 mm width roll
- Available customized



Specification

Printer Method	Thermal dot line
Dots/line	576 dot/line
Resolution (dots/mm)	8 sot/mm
Cutting method	Full/partial
Paper width	58 mm or 80 mm
Printing width	72
Roll diameter max	Φ80 mm
Paper thickness	0.052~0.12 mm
Printing speed	250 mm/s
Paper loading method	Easy loading
Printer head	Thermistor
Paper end	Photo interrupter
Working voltage (Vp)	DC 24V
Power consumption	2A (average)
Peak current	6.5A
Interface	RS-232C/USB
Commands	ESC/POS
Driver	Windows/Linux/Android/Raspberry Pi
Cutter life	1,500,000
Pulse	100,000,000
Work temperature	-10~50 °C

Work humidity	20% 85%RH
Storage temperature	-20~60 °C
Storage humidity	10~90%RH
Printing length (km)	Over 150
Dimension (mm)	127 x127 x 100
Weight (g)	900 (without paper roll)

Other Floor Mount Standee



Interactive Service Kiosk

Interactive Service Kiosk

Interactive Service Kiosk

We are also available @

**Delhi | Varanasi | Maldah | Siliguri
Bankura | Bhubaneshwar**

Follow us on    
@PremiumGlassignage

For further correspondence # +91 97761 98155 +91 94330 01288 | mail@capitalinfoart.com
Kolkata Corporate Office : 11/B, & 10, Chowringhee Terrace, Gokhale Road, Kolkata - 700 020 | INDIA
Experience Centre : **Crystal Studio**, 29/1A, Ramkrishna Samadi Road, Phoolbagan, Kolkata - 700 054
Central Workshop : 51A, Rashbehari Avenue, Kokata - 700 026 | INDIA
Factory / Warehouse : G1-10/ New Belwedanga Road, Behala, Shibarampur, Kolkata - 700 141 | INDIA
Maldah Experience Centre : **Kixi Media**, Jyoti Complex, Rabindra Avenue, Malda 732101, WB # 94341 54440
Bankura Experience Centre : **Galaxy**, Rampur Chhotokalitala, Bankura 722101, WB # 77970 14041