

OUTDOOR Digital Signage

capitalinfoart®

Enjoy seamless **Cloud Network**
for every single device with **FREE**
Content Management Software



Key Features

- **Open Android 11** and above
- **Signage** and **Third Party** Applications
- Content Management System by **LAN**
- Content Management System by **Cloud**
- **U-Disk/USB** Playback System
- **Audio** Outdoor with Metal Enclosure
- Vertical / Horizontal **Split Screen** available
- Creating Better Visions with **IP 65**

Application Area

Retail | Healthcare | Educational Institutions
Hotels & Restaurants Financial Institutions
Entertainment Zone | Corporate Area
Shopping Malls | Reception Area | Lounge Area

Sizes Available

43 | 55

www.capitalsignage.com

Display Panel Specifications

Features	Model No. CIA-430NT-WMOM	Model No. CIA-550NT-WMOM	Model No. CIA-430NT-FMOM	Model No. CIA-550NT-FMOM
Panel Size	43 inch	55 inch	43 inch	55 inch
Panel Type	IPS	IPS	IPS	IPS
Resolution	1080 x 1920 / 2160 x 3840	1080 x 1920 / 2160 x 3840	1080 x 1920 / 2160 x 3840	2160 x 3840
Contrast Ratio	3000 : 1	3000 : 1	3000 : 1	3000 : 1
Viewing Angle	170°	170°	170°	170°
Luminance	2500 nits	3000 nits	2500 nits	3000 nits
Aspect Ratio	16 : 9 9 : 16	16 : 9 9 : 16	9 : 16	16 : 9 9 : 16
Display colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors	1.07 G (8 bits - FRC)
Display mode	Transmission mode, Normally Black	Transmission mode, Normally Black	Transmission mode, Normally Black	Transmission mode, Normally Black
Active area (W x H) (mm)	532 x 943	684 x 1213	585 x 1040	680.4 x 1209.6
Operating Temperature	0 °C - +50 °C	0 °C - +50 °C	0 °C - +50 °C	0 °C - +50 °C
Storage Temperature	-20 °C - +60 °C	-20 °C - +60 °C	-20 °C - +60 °C	-20 °C - +60 °C
Operating Ambient Humidity	5%RH - 100%RH	5%RH - 100%RH	5%RH - 100%RH	5%RH - 100%RH
Protection Grade	IP 65	IP 65	IP 65	IP 65

Electrical & Physical Specifications

Electrical & Physical specification			CIA-430NT-WMOM	CIA-550NT-WMOM	CIA-430NT-FMOM	CIA-550NT-FMOM
Input Power Supply	220 V - 240 V 1 Ph. 50 Hz	Dimensions (W x D x H)	640 x 130 x 1140 (mm)	800 x 140 x 1480 (mm)	700 x 240 x 1980 (mm)	860 x 240 x 2160 (mm)
Operating Voltage	12 V DC	Base (W x D x H)			550 x 520 (mm)	750 x 575 (mm)
Standby	0.5 W	Gross Weight	60 kg	80 kg	128 kg	160 kg
		Cabinet Material	MS	MS	MS	MS

Hardware Specifications

CPU & Chipset	RK 2.0 Ghz & above 64 bit high performance CPU
GPU	Mali-G52 GPU supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.0 and Vulkan 1.1
Memory	Default 4 GB 8 GB (Optional)
Built-in storage capacity	Default 32 GB 64 GB (Optional)
Network	Adaptive 10/100 mbps 100/1000 mbps Ethernet
Wifi	Support 2.4G / 5G, Wi-Fi, support Wi-Fi 802.11b/g/n protocols
Image rotation	Support manual rotation of 0 degree, 90 degree, 180 degree, 270 degree
Display	TFT LCD Professional Signage Panel (Industrial Grade) 16.7M colours 8-bit colour depth 170° viewing angle 24 x 7 operation support Outdoor Metal Panel
HDMI	HDMI (Out) / HDMI (In) optional
Audio	2 x 25W speaker
Power amplifier	2 outputs (8 ohms, 25 watts dual audio amplifier output)
Microphone	Differential MIC input
Touch screen (Optional)	Support USB multi-point infrared touch, multi-point capacitive touch, multi-point nano film touch, multi-point acoustic wave touch, multi-point optical touch and more.
RCT	Built-in real-time clock function
USB	2 x USB (USB 3.0)
Infrared	Support infrared remote control function
LED	1* power status LED (green), 1* system LED (green / blue blinking in default)
Bluetooth	Support 4.2 bluetooth
I/O	Support 5 IO input and output control, can be used as key scanning control
Serial port	30 pin FPC interface, Largest support 1300 w Camera
Power Adapter	Input : AC 100-240 V 50-60 HZ, Output : DC 12 V 1.5 A (Requires surge voltage less than 18 V and ripple voltage less than 100 mV)
Optional hardware	Camera, Sensor, QR Scanner, Printer etc.

FLOOR MOUNT **DIGITAL KIOSK** Specification**Software specifications**

Operating system	Android 11.0 & above
Audio	Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP and other formats
Video	Support AVI, rm, rmvb, MKV, WMV, MOV, MP4, DAT, PMP, MPEG, MPG, FLV, ASF, TS, TP, 3GP, MPG and other formats
Image	Support various image formats such as JPG, BMP, PNG
System comes with application software	APK Installer, Email, Calculator, Browser, Recorder, Calendar, Settings, Clock, Video Player, Search, Contacts, Gallery, Download, Camera, Music, Explorer, etc.
Language	English / Hindi / Bengali (Support Multi-Language)
Input method	Standard Android Keyboard with optional third-party input method
System Management	Original ecological Android system, open root permissions, and can customize product development Real-time remote monitoring, system crash self-recovery, unattended 7 x 24 hours Support OTA remote upgrade; support U disk upgrade Support server / stand-alone mode switching Support WI-Fi hotspot
System watchdog	Support software watchdog

Available sizes 32 | 43 | 55 | 65 inch

Other Indoor Floor Mount Standee



Floor Mount Glass Kiosk



Interactive Service Kiosk



A-Type Digital Standee

We are also available @

Delhi | Varanasi | Maldah | Siliguri
Bankura | Bhubaneswar

Follow us on    
@PremiumGlassignage

For further correspondence # +91 97761 98155 +91 94330 01288 | mail@capitalinfoart.com
Kolkata Corporate Office : 11/B, & 10, Chowringhee Terrace, Gokhale Road, Kolkata - 700 020 | INDIA
Experience Centre : **Crystal Studio**, 29/1A, Ramkrishna Samadi Road, Phoolbagan, Kolkata - 700 054
Central Workshop : 51A, Rashbehari Avenue, Kokata - 700 026 | INDIA
Odisha Office & Exp. Centre : **Grand Bazaar**, Cuttack - Bhubaneswar Rd, Phulnakhara, Odisha 754001, # 91433 10059
Maldah Experience Centre : **Kixi Media**, Jyoti Complex, Rabindra Avenue, Malda 732101, WB, # 94341 54440
Bankura Experience Centre : **Galaxy**, Rampur Chhotokalitala, Bankura 722101, WB, # 77970 14041