



VCK 576 SERIES

Indoor & Outdoor Rental LED screen

www.capitalsignage.co Call Us: 9007773730






01 Product Overview


O2 Scorpe of Applications

03 Product Features

04 Product Specifications



Product Overview



Design for rental and indoor, outdoor appllications

Product Overview



VCK Series

Indoor: P3.6/4.8 Outdoor: P3.6/4.8 Super lightweight and slim 9.8 KG/ pcs


O Curve optional -10° +15°

Front/Rear Easy Maintenance 100%

Energy Saving Avg. 180 w/sqm

© Creative Installation Corner Optional 45°/pcs

capital<mark>infoart</mark>






Scorpe of Applications

Widely applications, curve and corner installations




Scorpe of Applications

- > Multi-assembly
- ➤Widely application
- ➤ Design for quick rental
- ➤ Curve or corner installations








Events, commercial shows, Conference, Performance, Advertising

Product Features







LED Module


Power box

Curved Lock


Apperance COMPACT APPERANCE

- Fancy slim cabinet, and Fast lock with one man installation design, save the strength and time
- Curve lock with -10 +15 degree
- Magnetic front service (Screw optional)
- Strengthen housing structure design, no deformation
- Anti fire / corrosion / ultra-violet material






- ✓ Optimized PCB board design
- ✓ 4 layers PCB
- ✓ Calibration-memo in PCB board
- ✓ Perfect matched with Novastar control system
- ✓ Perfect heat sinking





Calibration memo in LED module



Calibration



Typical and special solutions, Widely application



Hanging

Lighter weight and better thickness control of our cabinet with fast locks makes hanging more efficiently



Stacking

Rigid and strong stacking frame ensure the stability of product installation





CORNER PROTECTOR FROM HIT

Protector around four-corner of cabinet to better protect cabinet from led damage



HUB Card and Poxer Box use




capitalinfoart

- ► Curved design
- ➤ Power box easy removable
- ➤ Design for special using
- ► Corner for Square

FIRST CLASS FLATNESS

For VCK Series, the cabinet frame is produced by leading supplier for die-cast frames, well known in the industry for reliable quality control



www.capitalsignage.com

CONCAVE AND CONVEX INSTALLATIONS





Curve cabinet unique design

Display extraordinary LED effect and visual perception

www.capitalsignage.com

DISPLAY EFFECT


Refresh rate is up to 3840HZ, gray scale 14bit, displaying vividly



High Refresh Rate: 3840Hz

Common Refresh Rate

WIDE VISUAL ANGLE



Horizontal: 170 degree, vertical: 160 degree



PART. 04

Product Specifications

Design with fast rental and super slim





Specification

VCK models

| Pixel pitch | 2.57mm | 3.6mm | 3.6mm outdoor | 4.8mm outdoor |
|-------------------------|---|------------|---------------|---------------|
| LED configuration | SMD1515 | SMD2020 | SMD1921 | SMD1921 |
| Brightness | 1000 nits | 1000 nits | 4500 nits | 4500nits |
| Viewing angle | 170°/ 160° | 170°/ 160° | 170°/ 160° | 170°/ 160° |
| Scan mode | 1/16 | 1/28 | 1/16 | 1/13 |
| Refresh rate | 1920/3840/7680Hz | | | |
| Processing | 14/16 bits | 14/16 bits | 14/16 bits | 14/16 bits |
| Module size | 288mm x 288mm(W x H) | | | |
| Panel size | 576mm x 576mm x 75mm (W x H x D) | | | |
| Panel weight | 9.8kg/pcs | | | |
| Input voltage | AC100~240V 50/60 HZ | | | |
| Power consumption (Avg) | 160W/sqm | 160W/sqm | 180W/sqm | 180W/sqm |
| Power consumption (Max) | 600W/sqm | 600W/sqm | 640W/sqm | 640W/sqm |
| Working temperature | -20°C~60°C | | | |
| IP rating | IP42/IP31 | IP42/IP31 | IP65/IP54 | IP65/IP54 |
| Life span | 100,000 hrs | | | |
| Warranty | 24 months full warranty + 12 month free maintenance | | | |