capitalinfoart®

FLOOR MOUNT INTERACTIVE SERVICE KIOSK

With a wide range of Interactive & Non-Interactive Kiosk Solutions developed and fabricated by the expert designers of Capital Infoart in Mixed Medium are fully handcrafted for ethnic look and feel. This signage is powered by a Capacitive Touch Panel with an extraordinary touch feel for smoothest interaction.



Application Area

Healthcare | Educational Institutions | Galleria Hotels & Restaurants | Financial Institutions Entertainment Zone | Corporate Area Shopping Malls | Reception and Lounge Area

www.capitalinfoart.com

FLOOR MOUNT INTERACTIVE SERVICE KIOSK

Display Panel Specifications

Variable	27" [L14-PSM]	32" [L14-P5M]	43" [L14-PSM]
Panel Size	27 inch	32 inch	43 inch
Panel Type	IPS	IPS	IPS
Resolution	1080 x 1920	1080 x 1920	1080 x 1920 / 2160 x 3840
Contrast Ratio	1200:1	1200 : 1	1200:1
Viewing Angle	178°	178°	178°
Luminance	300 nits	400 nits	450 nits
Aspect Ratio	16:9 9:16	16:9 9:16	16:9 9:16
Display colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors
Display mode	Transmission mode, Normally Black	Transmission mode, Normal l y Black	Transmission mode, Normally Black
Active area (W x H)	336.1 x 597.6	392.8 x 698.4	529.25 x 940.89
Operating Temperature	0°C - +50°C	0°C - +50°C	0°C - +50°C
Storage Temperature	-20°C - +60°C	-20°C - +60°C	-20°C − +60°C
Operating Ambient Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH
Storage Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH

Electrical & Physical Specifications

Electrical & Physical specification		27"	32"	43"	
Input Power Supply	220 V - 240 V, 1 Ph. 50 Hz	Dimensions (W x D x H)	394.2 x 32.5 x 654 (mm)	449.7 x 42 x 750.4 (mm)	532.14 x 55 x 995.2 (mm)
Operating Voltage	12 V DC	Base (W x D x H)	700 x 350 x 1095 (mm)	700 x 350 x 1095 (mm)	700 x 350 x 1095 (mm)
Standby	0.5 W	Gross Weight	14 kg	15 kg	16 kg
		Cabinet Material	MS	MS	MS





Hardware Specifications

CPU RK 1.8 Ghz & above 64 bit high performance CPU GPU Mail-G55/T864/T764 (Optional) high performance GPU Default 2 GB | 4 GB (Optional) Memory **Build-in storage capacity** Default 16 GB | 32 GB Network Adaptive 10/100 mbps | 100/1000 mbps Ethernet Wifi Support 2.4G / 5G Wi-Fi, support Wi-Fi 802.11b/g/n protocols **Image rotation** Support manual rotation of 0 degree, 90 degree, 180 degree, 270 degree Display TFT LCD Professional Signage Panel (Industrial Grade) 16.7M colours 8-bit colour depth 178 degree viewing angle 24 x 7 operation support Ultra slim metal body **HDMI** HDMI (Out) / HDMI (In) optional **Audio** 10W x 2 speaker 2 outputs (8 ohms, 10 watts dual audio amplifier output) Power amplifier Microphone Differential MIC input **Touch screen (Optional)** Support USB multi-point infrared touch, multi-point capacitive touch, multi-point nano film touch, multipoint acoustic wave touch, multi-point optical touch and more. **RCT** Built-in real-time clock function USB 2 x USB (USB 3.0) Support infrared remote control function Infrared LED 1* power status LED (green), 1* system LED (green / blue blinking in default) **Bluetooth** Support 4.2 bluetooth I/O Support 5 IO input and output control, can be used as key scanning control Serial port 30 pin FPC interface, Largest support 1300 w Camera **Power Adapter** Input: AC 100-240 V 50-60 HZ, Output: DC 12 V 1.5 A (Requires surge voltage less than 18 V and ripple voltage less than 100 mV)



Software specifications

Operating system	Android 10.0 & above
Audio	Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP and other formats
Video	Support AVI, rm, rmvb, MKV, WMV, MOV, MP4, DAT, PMP, MPEG, MPG, FLV, ASF, TS, TP, 3GP, MPG and other formats
lmage	Support various image formats such as JPG, BMP, PNG
System comes with application software	APK Installer, Email, Calculator, Browser, Recorder, Calendar, Settings, Clock, Video Player, Search, Contacts, Gallery, Download, Camera, Music, Explorer, etc.
Language	Support multi-language
Input method	Standard Android Keyboard with optional third-party input method
System Management	Original ecological Android system, open root permissions, and can customize product development Real-time remote monitoring, system crash self-recovery, unattended 7 x 24 hours Support OTA remote upgrade; support U disk upgrade Support server / stand-alone mode switching Support WI-Fi hotspot
System watchdog	Support software watchdog

Available sizes 27 | 32 | 43 inch

Other Floor Mount Standee





We are also available @

Delhi | Ghaziabad | Varanasi | Maldah Siliguri | Bankura | Bhubaneshwar

For further correspondence # +91 97761 98155 +91 94330 01288 | mail@capitalinfoart.com Kolkata Corporate Office: 11/B, Chowringhee Terrace, Gokhale Road, Kolkata - 700 020 | INDIA Kolkata Corporate Experience Centre: 10, Chowringhee Terrace, Bhowanipore, Kolkata - 700 020 | INDIA

Kolkata Workshop : 51A, Rashbehari Avenue, Kokata - 700 026 | INDIA

Kolkata Factory: G1-10/ New Belwedanga Road, Behala, Shibarampur, Kolkata - 700 141 | INDIA U.P. Office: 5A-70 Cloud 9 Tower, Vaishali, Sector 1, Ghaziabad, Uttar Pradesh - 201010 | #+91 9161006555 | INDIA

Maldah Experience Centre & Office : Jyoti Complex, Rabindra Avenue, Malda 732101, West Bengal | INDIA