

# FLOOR MOUNT DIGITAL KIOSK

With a wide range of Interactive & Non-Interactive Kiosk Solutions developed and fabricated by the expert designers of **Capital Infoart** in Mixed Medium are fully handcrafted for ethnic look and feel. The fascia is fabricated with printed glass in the front and mounted on wheels for elegant outlook.



## Key Features

- **Open Android 10** and above
- **Signage** and **Third Party** Applications
- Content Management System by **LAN**
- Content Management System by **Cloud**
- **U-Disk/USB** Playback System
- Built-in **Audio**
- Slimmest digital standee with just **28 mm** thickness along with front glass fascia
- Vertical / Horizontal **split screen** available

## Application Area

Retail | Healthcare | Educational Institutions  
Hotels & Restaurants | Financial Institutions  
Entertainment Zone | Corporate Area  
Shopping Malls | Reception Area | Lounge Area

## Sizes Available

32 | 43 | 55

FLOOR MOUNT **DIGITAL KIOSK****Display Panel Specifications**

Variable	32" [K32-FL02-GSM]	43" [K43-FL02-GSM]	55" [K55-FL02-GSM]
Panel Size	32 inch	43 inch	55 inch
Panel Type	IPS	IPS	IPS
Resolution	1080 x 1920	1080 x 1920 / 2160 x 3840	1080 x 1920 / 2160 x 3840
Contrast Ratio	1200 : 1	1200 : 1	1200 : 1
Viewing Angle	178°	178°	178°
Luminance	400 nits	450 nits	500 nits
Aspect Ratio	16 : 9   9 : 16	16 : 9   9 : 16	16 : 9   9 : 16
Display colors	16.7 M (8 bits - true) colors	16.7 M (8 bits - true) colors	1.07 G (8 bits - FRC)
Display mode	Transmission mode, Normally Black	Transmission mode, Normally Black	Transmission mode, Normally Black
Active area (W x H)	392.8 x 698.4	529.25 x 940.89	680.4 x 1209.6
Operating Temperature	0°C - +50°C	0°C - +50°C	0°C - +50°C
Storage Temperature	-20°C - +60°C	-20°C - +60°C	-20°C - +60°C
Operating Ambient Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH
Storage Humidity	10%RH - 80%RH	10%RH - 80%RH	10%RH - 80%RH

**Electrical & Physical Specifications**

Electrical & Physical specification		32"	43"	55"	
Input Power Supply	220 V - 240 V, 1 Ph. 50 Hz	Dimensions (W x D x H)	470 x 47 x 1635 (mm)	600 x 40 x 1750 (mm)	800 x 40 x 1950 (mm)
Operating Voltage	12 V DC	Base (W x D x H)	485 x 450 (mm)	550 x 520 (mm)	750 x 575 (mm)
Standby	0.5 W	Gross Weight	30 kg	40 kg	48 kg
		Cabinet Material	MS	MS	MS

# FLOOR MOUNT **DIGITAL KIOSK**

## Hardware Specifications

<b>CPU</b>	RK 1.8 Ghz & above 64 bit high performance CPU
<b>GPU</b>	Mail-G55/T864/T764 (Optional) high performance GPU
<b>Memory</b>	Default 2 GB   4 GB (Optional)
<b>Build-in storage capacity</b>	Default 16 GB   32 GB
<b>Network</b>	Adaptive 10/100 mbps   100/1000 mbps Ethernet
<b>Wifi</b>	Support 2.4G / 5G Wi-Fi, support Wi-Fi 802.11b/g/n protocols
<b>Image rotation</b>	Support manual rotation of 0 degree, 90 degree, 180 degree, 270 degree
<b>Display</b>	TFT LCD Professional Signage Panel (Industrial Grade) 16.7M colours 8-bit colour depth 178 degree viewing angle 24 x 7 operation support Ultra slim metal body
<b>HDMI</b>	HDMI (Out) / HDMI (In) optional
<b>Audio</b>	10W x 2 speaker
<b>Power amplifier</b>	2 outputs (8 ohms, 10 watts dual audio amplifier output)
<b>Microphone</b>	Differential MIC input
<b>Touch screen (Optional)</b>	Support USB multi-point infrared touch, multi-point capacitive touch, multi-point nano film touch, multi-point acoustic wave touch, multi-point optical touch and more.
<b>RCT</b>	Built-in real-time clock function
<b>USB</b>	2 x USB (USB 3.0)
<b>Infrared</b>	Support infrared remote control function
<b>LED</b>	1* power status LED (green), 1* system LED (green / blue blinking in default)
<b>Bluetooth</b>	Support 4.2 bluetooth
<b>I/O</b>	Support 5 IO input and output control, can be used as key scanning control
<b>Serial port</b>	30 pin FPC interface, Largest support 1300 w Camera
<b>Power Adapter</b>	Input : AC 100-240 V 50-60 HZ, Output : DC 12 V 1.5 A (Requires surge voltage less than 18 V and ripple voltage less than 100 mV)


# FLOOR MOUNT DIGITAL KIOSK

## Software specifications

<b>Operating system</b>	Android 10.0 & above
<b>Audio</b>	Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP and other formats
<b>Video</b>	Support AVI, rm, rmvb, MKV, WMV, MOV, MP4, DAT, PMP, MPEG, MPG, FLV, ASF, TS, TP, 3GP, MPG and other formats
<b>Image</b>	Support various image formats such as JPG, BMP, PNG
<b>System comes with application software</b>	APK Installer, Email, Calculator, Browser, Recorder, Calendar, Settings, Clock, Video Player, Search, Contacts, Gallery, Download, Camera, Music, Explorer, etc.
<b>Language</b>	Support multi-language
<b>Input method</b>	Standard Android Keyboard with optional third-party input method
<b>System Management</b>	Original ecological Android system, open root permissions, and can customize product development Real-time remote monitoring, system crash self-recovery, unattended 7 x 24 hours Support OTA remote upgrade; support U disk upgrade Support server / stand-alone mode switching Support WI-Fi hotspot
<b>System watchdog</b>	Support software watchdog

Available sizes 32 | 43 | 55 inch

Other Floor Mount Standee



Floor Mount Glass Kiosk



Interactive Service Kiosk



A-Type Digital Standee

We are also available @

**Delhi | Ghaziabad | Varanasi | Malda  
Siliguri | Bankura | Bhubaneshwar**

Follow us on    

@PremiumGlassignage

For further correspondence # +91 97761 98155 +91 94330 01288 | mail@capitalinfoart.com  
Kolkata Corporate Office : 11/B, Chowringhee Terrace, Gokhale Road, Kolkata - 700 020 | INDIA  
Kolkata Corporate Experience Centre : 10, Chowringhee Terrace, Bhowanipore, Kolkata - 700 020 | INDIA  
Kolkata Workshop : 51A, Rashbehari Avenue, Kolkata - 700 026 | INDIA  
Kolkata Factory : G1-10/ New Belwedanga Road, Behala, Shibarampur, Kolkata - 700 141 | INDIA  
U.P. Office : 5A-70 Cloud 9 Tower, Vaishali, Sector 1, Ghaziabad, Uttar Pradesh - 201010 | #+91 9161006555 | INDIA  
Maldah Experience Centre & Office : Jyoti Complex, Rabindra Avenue, Malda 732101, West Bengal | INDIA